Doc Code: AP.PRE.REQ PTO/SB/33 (01-09)
Approved for use through 02/28/2009. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PRE-APPEAL BRIEF REQUEST FOR REVIEW		Docket Number (Optional)		
		03-087 (US01)		
I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to "Mail Stop AF, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450" [37 CFR 1.8(a)]	Application Number		Filed	
	10/626,246 7/24/03		7/24/03	
on May 24, 2010	First Named Inventor			
Signature_/NancyRushton/	Christopher J. Elliott			
	Art Unit		Examiner	
Typed or printed Nancy Rushton name	3731		Elizabeth Houston	
Applicant requests review of the final rejection in the above-identified application. No amendments are being filed with this request. This request is being filed with a notice of appeal. The review is requested for the reason(s) stated on the attached sheet(s). Note: No more than five (5) pages may be provided.				
l am the applicant/inventor. assignee of record of the entire interest. See 37 CFR 3.71. Statement under 37 CFR 3.73(b) is enclosed. (Form PTO/SB/96) ✓ attorney or agent of record. Registration number 37 CFR 1.34.		d T. Burse Typed 777-2905 Tele	Signature or printed name phone number	
Registration number if acting under 37 CFR 1.34	May 24, 2010			
Registration number if acting under 37 CFR 1.34 Date NOTE: Signatures of all the inventors or assignees of record of the entire interest or their representative(s) are required. Submit multiple forms if more than one signature is required, see below*.				

This collection of information is required by 35 U.S.C. 132. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11, 1.14 and 41.6. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop AF, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

*Total of

forms are submitted.

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

- The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
- 2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
- A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
- 4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
- 5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
- 6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
- 7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
- 8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
- A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Attorney Docket: 03-0087 US01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of:)
Christopher J. Elliott	Confirmation No.: 1009
Serial No. : 10/626,246	Group Art Unit: 3731
Filed: July 24, 2003	Examiner: Houston, Elizabeth
For: Embolic Coil)
)

PRE-APPEAL BRIEF REQUEST FOR REVIEW

Mail Stop: **AF**

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Dear Sir:

Applicants respectfully request a pre-appeal brief conference. No amendments are being filed with this request. Claims 1, 2, 6-12, 24 and 26-29 remain pending in this application. Claims 1, 2, 6-10, 24 and 26 stand rejected under 35 U.S.C. §103(a), as allegedly being unpatentable over U.S. Patent No. 5,980,514 ("Kupiecki") in view of U.S. Patent No. 5,382,260 ("Dormandy"). Claims 11, 12 and 27-29 stand rejected under 35 U.S.C. §103(a), as allegedly being unpatentable over Kupiecki in view of Dormandy, in further view of U.S. Patent No. 6,171,326 ("Ferrera").

Independent claim 1 recites an embolic coil comprising "an elongated core element formed of a shape memory material and movable between a straightened first configuration and a shape memorized second coiled configuration; an elongated outer element which, in the first configuration, is wound around the elongated core element to form a primary coil; and *a plurality of fibers frictionally gripped between adjacent coils of the primary coil*." (Emphasis added). Claims 2-12 depend from claim 1, and thus include these same limitations. Independent claim 24 similarly recites a coiled medical device comprising a primary coil having a primary coil shape, and a secondary coil formed of a shape memory material and disposed in a lumen extending through the primary coil, the secondary coil having a secondary coil memorized shape, the device further comprising "a plurality of fibers gripped between adjacent coils of the primary

Attorney Docket: 03-0087 US01

coil and held therebetween by friction." (Emphasis added). Claim 26 depends from claim 24, and thus includes these same limitations. An explanation of the claimed frictional fiber retention aspects of the devices of claims 1 and 24 is set forth in paragraphs 16 and 17 of the specification:

[0016] FIG. 4 shows an exemplary embodiment of fibers 22 being attached to the primary coil 54 of an embolic coil. As indicated above, the fibers 22 may be polymeric fibers or may be made of other flexible materials, for example, Nitinol. The fibers 22 are added to the platinum primary coil 54 to impart greater thrombogenicity to the overall embolic coil, and to increase its ability to stop the undesired flow of blood therethrough. The fibers 22 are generally inserted between the loops 56 of the primary coil 54, and are held in place by virtue of the cold work imparted to the platinum wire during the primary coil winding process. In an exemplary embodiment, the insertion of the fibers 22 in the loops 56 is carried out after the heat treatment used to set and maintain the shape of the secondary coil 62.

[0017] However, other processes may be better suited to forming embolic coils having enhanced shape retention and fiber retention properties. Specifically, the retention of the fibers 22 between the loops 56 of the primary coil 54 is a function of the amount of cold work that has been performed and that continues to affect the platinum wire 50. In other words, the fibers 22 remain in place more securely when a large amount of cold work is performed that is not later removed. ***


(Emphasis added).

Independent claim 27 recites an embolic coil comprising "an elongated core element formed of a shape memory material treated to define a memorized secondary coil shape, the elongated core including a plurality of fiber retention grooves formed in an outer surface thereof; an elongated outer element wound around the elongated core element to define a primary coil shape of the embolic coil; and a *plurality of fibers held* within the first fiber retention grooves." (Emphasis added). Claims 28 and 29 depend from claim 27, and thus includes these same limitations. An explanation of the claimed frictional fiber retention aspects of the device of claim 27 is set forth in paragraph 28 of the specification (with reference to Figs. 7 and 8):

[0028] Additional enhancements may be made to the embolic coil according to the present invention, to improve the device's fiber retention properties. For example, as shown in FIG. 7, the shape memory core wire 120 may comprise cylindrical grooves 124 that are used as anchors for fibers. Grooves 124 channel the fiber bundles around core wire 120, so that they are held in place by the core wire 120. In this manner the primary coil 108 is freed from that function. Channeling the fiber bundles via grooves 124 promotes cohesion of the fibers, and reduced the loss of fibers during use of the embolic coil. In a different embodiment shown in FIG. 8, a shape memory core wire 122 may comprise spiral grooves 126, which also help anchor fibers such as the fibers 22 shown in FIG. 4. In these embodiments, the amount of

cold work imparted to the primary coil 108 has less effect on how well the fibers 22 are retained, and fewer restrictions are imposed on the shape and properties of the primary coil 108.

The Examiner has correctly stated that Kupiecki does not teach or suggest the attachment of fibers to the coil device be any means, and cites Dormandy in support of the rejection. However, Dormandy does not teach that the fibers are "frictionally gripped between adjacent coils of the primary coil," as recited in claim 1, or "gripped between adjacent coils of the primary coil and held therebetween by friction," as recited in claim 24, but instead that the fibers (22) are wound around turns of the coil, and held in place by a loop (23) formed by the winding. (See Dormandy, col. 3, lines 50-60, "loop 23 serves as the sole means for retaining the group 21 of fibers 22 on the coil 12."). This is clearly shown in Figs. 3 and 4 of Dormandy:



It is respectfully submitted that the fibers (22) of Dormandy are not frictionally gripped between adjacent coils of the coil (12), especially in light of the fact that adjacent turns of the coil (12) are shown to be spaced from one another. Nor does Dormandy teach or suggest that adjacent turns of the coil (12) are wound tightly against one another. Moreover, the modification of Kupiecki proposed by the Examiner provides unexpected results. Dormandy teaches fibers (22) that are wound around turns of the coil (12) to form a loop (23) by inserting a first free end of the fiber (22) between two turns of a coil and into a cavity located within the coil (12) and the free end is then looped around a turn of the coil and inserted back into the cavity before being drawn out of the coil (12) one last time. It is unclear how incorporating the fibers (22) of Dormandy into the coil device of Kupiecki would result in the device of independent claims 1 or 24, since the fibers (22) of Dormandy cannot be looped around the wire (202) of Kupiecki due to obstruction by the inner core member (204). (See Kupiecki, col. 14, Il. 3 - 45; Fig.8).


In order to achieve the desired helical shape, to the wire (202) of Kupiecki must be wound in a tight configuration over the inner core member (204) as a loose winding is incapable of imparting the desired coiled shape. However, Kupiecki states that the wire (202) is secured to the outer body of the inner core member (204) by welding the contacting ends thereof together, thus confirming that the wire (202) is wound tightly over the inner core member (204) so that the resulting coil is held in a contacting configuration therewith. (*Id.* at col. 14, 1l. 26 - 32). Thus, the modification proposed by the Examiner would not result in the claimed invention, and it is respectfully submitted that neither Kupiecki nor Dormandy, taken either alone or in combination, disclose or suggest an embolic coil comprising a plurality of fibers that are "frictionally gripped between adjacent coils of the primary coil," as recited in claim 1, or "gripped between adjacent coils of the primary coil and held therebetween by friction," as recited in claim 24. According, it is respectfully requested that the rejection of claims 1, 2, 6-10, 24 and 26 over Kupiecki, in view of Dormandy, be withdrawn.


Regarding claims 11 and 12 (which depend from claim 1), it is respectfully submitted that Ferrera also does not disclose or suggest an embolic coil having a plurality of fibers that are "frictionally gripped between adjacent coils of the primary coil." According, it is respectfully requested that the rejection of claims 1, 2, 6-10, 24 and 26 over Kupiecki, in view of Dormandy, and in further view of Ferrera, be withdrawn.

Regarding claims 27-29, it is further respectfully submitted that Ferrera does not disclose or suggest an embolic coil comprising "an elongated core element formed of a shape memory material treated to define a memorized secondary coil shape, the elongated core including *a plurality of fiber retention grooves formed in an outer surface thereof*; an elongated outer element wound around the elongated core element to define a primary coil shape of the embolic coil; and a *plurality of fibers held within the first fiber retention grooves*." (Emphasis added).

The Examiner states that "the resultant combination of Ferrera's multi-stranded cable with the base [Kupiecki] device provides fiber retention grooves as claimed (Note the circumferential and spiral grooves formed between each strand in Fig. 4, as well as the circumferential and spiral groove formed by the wrapped cover (56) in Figs. 10a and 10b)." However, it can be plainly seen in the referenced figures of Ferrera that the spaces

between the cables do <u>not</u> comprise a plurality of fiber retention grooves formed in an outer surface of an elongated core element, as required by independent claim 27:





Respectfully submitted,

VISTA IP LAW GROUP LLP

Dated: May 24, 2010 By: /DavidTBurse/

David T. Burse Reg. No. 37,104

VISTA IP LAW GROUP LLP

Customer 12930 Saratoga Avenue, Suite D-2

Number Saratoga, CA 95070 **41696** Phone (408) 777-2905 Fax (408) 877-1662

PATENT Fax (408) 87 TRADEMARK OFFICE